



## FIVE OUTLET MANIFOLD BLOCK (1500 BAR)

The maximum working pressure for this five outlet Manifold Block is 1500 bar. The manifold block is assembled with self sealing quick connectors for fast and clean operation.

The quick connectors are fitted with plastic dust caps. Each manifold block is filled with oil and pressure tested prior to dispatch. Test certificates are supplied.

All manifolds are identified by serial numbers. They conform to the requirements of the European Pressure Equipment Directive and are CE marked.

This manifold block can be used to drive five tools simultaneously. When used in conjunction with BT-1580 it is ideally suited to the connection of eight hydraulic tools for simultaneous operation. Alternatively, when using four tools a pressure gauge can be connected to the central outlet.

Any number of these manifold blocks may be connected together, either by direct connection or with a flexible hose connected between the blocks. This manifold block is also available with 1500 bar swivels fitted to the outlet connectors.

### LEGEND

- A. Five outlets via self sealing quick connect coupling, fitted with plastic dust caps.
- B. Inlet via self sealing quick connect nipple fitted with a plastic dust cap.

(See also data sheets BT-1580 and DS-612.)  
(Quick connectors are Type B, see data sheet DS-26 for details.)

HYTORC owns all content, copyrights, trademarks and patents in this document. © 2020 HYTORC. Any unauthorized use or distribution of any material from this document is strictly prohibited.

# HYTORC